

5-10 Watts	10-12 Watts	12-18 Watts	20-36 Watts	36-60 Watts	60-120 Watts	120-180 Watts	Open Frame
<p><b>GT-83083-0505-USB</b> 5 Watts Vout=5 49.2 x 47.0 x 27.5</p>	<p><b>GT-86120-WWVV</b> 10 Watts Vout=5, 12 70 x 32.8 x 48.5</p>	<p><b>GT-86120-WWVV-X.X-W2E</b> 12 Watts Vout=5, 12 69 x 28.8 x 58.3</p>	<p><b>GTM93021-20VV-P2</b> 20 Watts Vout=5-48 51.0x48.0x35.0</p>	<p><b>GTM96300-36VV-R2/R3A</b> 36 Watts Vout=5-48 74 x 43.5 x 36.8</p>	<p><b>GTM96600-60VV-R</b> 60 Watts Vout=5-48 117.53 x 53.47 x 36.6</p>	<p><b>GTM43004P-WWVV-X.X-P3</b> 120 Watts Vout=5-48 178.0x76.0x39.5</p>	<p><b>GTM43004P-WWVV-X.X-F</b> 120 Watts Vout=5-48 184.0 X 62.0 X 37.5</p>
<p><b>GTM96060-06VV-Q</b> 6 Watts Vout=3.3-48 43.5 x 74.0 x 36.8</p>	<p><b>GTM46101-10VV-X.X-USB</b> 10 Watts Vout=5-5.5 41.0 x 71.0 x 31.5</p>	<p><b>GTM46161-16VV-X.X-USB</b> 16 Watts Vout=5-5.5 41.0 x 71.0 x 31.5</p>	<p><b>GT-46240-24VV</b> 24 Watts Vout=12-24 80.6 x 50.0 x 31.0</p>	<p><b>GT-96300-3656-AP</b> 36 Watts Vout=56 107 x 55 x 36</p>	<p><b>GTM91099-60VV-P3</b> 60 Watts Vout=5-48</p>	<p><b>GTM961600P-180VV</b> 180 Watts Vout=12-54 173 x 72 x 38</p>	<p><b>GTM43007-AWWVV-F</b> 60 Watts Vout=5-48 76.2 x 50.8 x 23.6 with heat sink 76.2 x 50.8 x 22.5 without heatsink</p>
<p><b>GT-46060-06VV-X.X-Q</b> 6 Watts Vout=5-24 40.5 x 64.0 x 30.0</p>	<p><b>GT-86120-WWVV-X.X-W2C</b> 12 Watts Vout=5, 12 69 x 28.8 x 40.3</p>	<p><b>GT-96180-1856-R2-AP</b> 18 Watts Vout=56</p>	<p><b>GT-86240-WWVV-X.X</b> 24 Watts Vout=12 73.5 x 35 x 57</p>	<p><b>GT-46401-40VV-X.X-Q</b> 40 Watts Vout=12-48 90.0 x 38.0 x 59.4</p>	<p><b>GT-96600-7056-T3-AP</b> 70 Watts Vout=56 165x32.5x56.5</p>	<p>Open Frame</p> <p><b>GTM41134-WWVV-F</b> 6 Watts Vout=3.3-48 84.5 x 41.5 x 17.0</p>	<p><b>GTM43007-BWWVV-F</b> 60 Watts Vout=5-48 101.6 x 50.8 x 22.5</p>
<p><b>GT-86060-06VV-X.X-W2</b> 6 Watts Vout=5, 12 66.5 x 25.5 x 51.3</p>	<p><b>GT-86120-WWVV-X.X-W2</b> 12 Watts Vout=5, 12 69 x 28.8 x 40.3</p>	<p><b>GTM96180-18VV</b> 18 Watts Vout=5-48 74x43.5x36.8</p>	<p><b>GTM91120CC-30VV-P2</b> 30 Watts Vout=5-48 102x46x37</p>	<p><b>GT-46400-40VV-X.X</b> 40 Watts Vout=12-48 111 x 52 x 32.3</p>	<p><b>GTM96900P90VV-X.X</b> 90 Watts Vout=12-54 149.38 x 62.6 x 33.5 ±1.0</p>	<p><b>GTM41080-18VV-F</b> 18 Watts Vout=5-48 74 x 44 x 34</p>	<p><b>GTM96700-BWWVV-F</b> 70 Watts Vout=5-48 101.6 x 50.8 x 30.5</p>
<p><b>GT-83084-10VV-USB</b> 10 Watts Vout=5-5.2 51.5 x 23.5 x 38.5 ±0.3</p>	<p><b>GT-46120-12VV-X.X</b> 12 Watts Vout=5-48 64.0 x 40.5 x 31.5</p>	<p><b>GTM96180-18VV</b> 18 Watts Vout=4-48 74 x 43.5 x 36.8</p>	<p><b>GT-83082-3612-W2/W2E</b> 36 Watts Vout=12 93 x 33 x 78.69±0.5</p>	<p><b>GTM96600-60VV</b> 60 Watts Vout=5-54 117.5 x 53.5 x 34.2</p>	<p><b>GTM961200P-120VV</b> 120 Watts Vout=12-54 149.30 x 62.80 x 34.0</p>	<p><b>GTM91120-30VV-FW</b> 30 Watts Vout=5-48 102 x 46 x 37</p>	<p><b>GTM91110P240XX</b> 240 Watts Vout=12-55 127 x 76 x 43</p>

### Battery Packs

#### BL0105F2635161S1PCAT

Lithium Polymer  
3.7VDC, 105mAh  
Battery Pack  
Dimensions:  
2.8 x 16.5 x 37  
Configuration: 1S 1P  
Cell Type: ICR18650-26F  
Cell Shape: Rectangular  
IEC 62133 Certified



#### BL1880F6835661S5PX9M

Lithium Polymer  
3.7VDC, 9400mAh  
Battery Pack  
Dimensions:  
185.5 x 69.5 x 7.9 mm  
10K NTC Thermistor  
BQ27200  
Configuration: 1S 5P  
Cell Type: GP683566  
Cell Shape: Rectangular  
IEC 62133 Certified



#### BL0750F5030481S1PCMC

Lithium Polymer  
3.7VDC, 700mAh  
Battery Pack  
Dimensions:  
50.5 x 30.5 x 5.3  
10K NTC Thermistor  
Configuration: 1S 1P  
Cell Type: GP503048  
Cell Shape: Rectangular  
IEC 62133 Certified  
UL 2054 Certified




#### Custom Battery Packs

Contact GlobTek with your specifications



#### BL1200P4054481S1PCAC

Lithium Polymer  
3.7VDC, 1200mAh  
Battery Pack  
Dimensions:  
53.0 x 48.0 x 4  
10K NTC Thermistor  
Configuration: 1S 1P  
Cell Type: GP404852  
Cell Shape: Rectangular  
IEC 62133 Certified



#### BL2600C18654S1PXX

Lithium Ion  
14.8VDC, 2600mAh  
Battery Pack Dimensions: 77 x 69  
Fuel Gauge  
Configuration: 4S 1P  
Cell Type: ICR18650-26F  
Cell Shape: Cylindrical  
IEC 62133 Certified



#### BL2200F6034501S2XXXX

Lithium Ion  
3.7VDC, 2200mAh  
Battery Pack  
Dimensions: 51 x 34 x 13  
Configuration: 1S 2P  
Cell Type: 603450  
Cell Shape: Rectangular  
IEC 62133 Certified



#### BL2600C1865004S1PG1

Lithium Ion  
14.8VDC, 2600mAh  
Battery Pack  
Dimensions:  
66 x 73.5 x 28.5  
Fuel Gauge/Built In  
Charger Circuitry  
4S 1P  
Cell Type: ICR18650-26F  
Cell Shape: Cylindrical  
IEC 62133 Certified



#### BL2600C1865001S2PXXXX

Lithium Ion  
3.7VDC, 5200mAh  
Battery Pack  
Dimensions:  
19 x 68.5 x 37  
Configuration: 1S 2P  
Cell Type: ICR18650-26F  
Cell Shape: Cylindrical  
IEC 62133 Certified



#### GTM91128

Smart Battery Charger  
Available in versions delivering 4.2V, 8.4V, or 12.6V at 1A to address single or multiple battery configurations



### International Power Cords

#### Type 451

North America  
NEMA 1-15P  
10A, 13A/125V~



#### Type 302

North America  
NEMA 5-15P  
10A, 13A/15A/125V~



#### Type 119

North America  
NEMA 5-15P Hospital Grade  
10A, 13A/15A/125V~



#### Type 703

IEC 60320-C7  
2.5A/250V~



#### Type 701

IEC 60320-C13  
10A, 13A, 15A  
125V~, 250V



#### Type 712

IEC 60320-C5  
2.5A, 10A/250V~



#### Type 7033

IEC 60320-C19  
12A, 14A, 16A  
125~250V



#### Type 705

IEC 60320-C14  
10A, 13A, 15A/250V~



#### Type PZ0800

United Kingdom  
BS1363  
13A/250V~



#### Type 207

"Europlug"  
CEE7 Standard XVI  
(CEE 7/16)  
2.5A/250V



#### Type 2314

Schuko Europe  
CEE7 Standard sh 7  
16A/250V



#### Type 550

Australia, New Zealand  
AS/NZS 3112  
10A/250V~



#### Type 205

India IS 1293  
6A/250V~



#### Type 208

South Africa SABS 164-1  
16A/250V~



#### Type 219

Argentina IRAM 2073  
10A/250V~



#### Type 204B

Brazil NBR 14136  
10A/250V~



#### Type 602

China GB 1002  
10A/250V~



#### Type 377C

Israel  
16A/250V~



#### Type 2302

Italy CEI 23-16  
10A/250V~



#### Type 2313K

Korea KS C 8305  
16A/250V~

