

<p>L Type Coaxial 5.5x2.5mm plug</p>	<p>YL3 Type Locking Kycon KPP-3P</p>	<p>DC Output Cord with In-Line Molded LED Indicator Light</p>	<p>TE Amp Connector 4 Position Rectangular Plug Connector IDC Tin 22 AWG</p>	<p>2464 Round Wire with Ferrite 3 Wires Stripped & Tinned</p>	<p>Round UL Type 22 AWG AWM 2661 Lumberg RSMV 3-657/2M Male Connector</p>	<p>IP68 Waterproof Jack (KCC Universal)</p>
<p>C Type Coaxial 5.5x2.1mm plug</p>	<p>YL4 Type KPPX-4P</p>	<p>Phoenix Contact Pluggable Terminal Blocks 2 Position 3.81 Pitch Plug</p>	<p>JST 3 Position Rectangular Housing Connector Receptacle. Natural 0.079" (2.00mm)</p>	<p>UL 1185 3 Pin DC Jack Connector FX9-3/C9581</p>	<p>2464, 1185 5 Pin Male DIN Connector</p>	<p>Flat 22 AWG Female USB 2.0 with Ferrite</p>
<p>K Type Coaxial 3.5x1.3mm plug</p>	<p>MSB Type Micro USB</p>	<p>Switchcraft Connector Standard Power Jack with Right Angle Overmold</p>	<p>Round 1185 18 AWG White Right Angle 2.5 x 5.5 x 11mm Spring Loaded Locking with Notch</p>	<p>Round Wire 5 Pin USB, Female</p>	<p>AWM 1/8 8 Pin Male DIN Connector</p>	<p>Right Angle USB 2.0 Micro and Mini Adaptor</p>
<p>LL Type 5.5x2.5mm Locking 760k type</p>	<p>USBC Type USB Type C</p>	<p>Switchcraft Connector Standard Power Jack with Right Angle Overmold</p>	<p>Flat SPT-1 20 AWG Stripped & Tinned</p>	<p>16, 18, 1185 AWG Locking Kycon 4 Pin Male Connector</p>	<p>UL 2464 18 AWG 8 Pin Male Mini DIN Connector</p>	<p>Lumberg Straight 3 Pin DIN Connector</p>
<p>CL Type 5.5x2.1mm Locking S761k type</p>	<p>Magnetic Connector</p>	<p>Custom Overmold Connector</p>	<p>Round Wire USB-A Male Cable</p>	<p>2464 18 AWG Quick Disconnect Terminal</p>	<p>16, 18, 1185 AWG Locking & Unlocking Kycon Mini DIN 6 Pin Male</p>	<p>Male 9 Pin D-Sub Connector</p>
<p>EJ1/2/3/4/5 EIAJ RC-5320A type connectors</p>	<p>Inquire for custom design</p>	<p>IP68 Waterproof Plug KCC Universal</p>	<p>USB 2.0 Male to B Male Cable</p>	<p>Flat 2468 20 AWG with Black & Red Alligator Clips</p>	<p>SPT-1 18 AWG with On/Off Switch with LED Indicator Light Stripped & Tinned</p>	

Connectors	Battery Packs		International Power Cords			
<p>Cigarette Lighter Socket</p> 	<p>BL0105F2635161S1PCAT Lithium Polymer 3.7VDC, 105mAh Battery Pack Dimensions: 2.8 x 16.5 x 37 Configuration: 1S 1P Cell Type: ICR18650-26F Cell Shape: Rectangular</p> 	<p>BL1880F6835661S5PX9M Lithium Polymer 3.7VDC, 9400mAh Battery Pack Dimensions: 185.5 x 69.5 x 7.9 mm 10K NTC Thermistor BQ27200 Configuration: 1S 5P Cell Type: GP683566 Cell Shape: Rectangular IEC 62133 Certified</p> 	<p>Type 451 North America NEMA 1-15P 10A, 13A/125V~</p> 	<p>Type 302 North America NEMA 5-15P 10A, 13A/15A/125V~</p> 	<p>Type 119 North America NEMA 5-15P Hospital Grade 10A, 13A/15A/125V~</p> 	<p>Type 703 IEC 60320-C7 2.5A/250V~</p> 
<p>Black Feed Through Rocker Switch</p> 	<p>BL0750F5030481S1PCMC Lithium Polymer 3.7VDC, 700mAh Battery Pack Dimensions: 50.5 x 30.5 x 5.3 10K NTC Thermistor Configuration: 1S 1P Cell Type: GP503048 Cell Shape: Rectangular IEC 62133 Certified UL 2054 Certified</p> 	<p>Custom Battery Packs Contact GlobTek with your specifications</p> 	<p>Type 701 IEC 60320-C13 10A, 13A, 15A 125V~, 250V</p> 	<p>Type 712 IEC 60320-C5 2.5A, 10A/250V~</p> 	<p>Type 7033 IEC 60320-C19 12A, 14A, 16A 125~250V</p> 	<p>Type 705 IEC 60320-C14 10A, 13A, 15A/250V~</p> 
<p>LEMO-K Connector Push-Pull High Density FGG.1K Connector</p> 	<p>BL1200P4054481S1PCAC Lithium Polymer 3.7VDC, 1200mAh Battery Pack Dimensions: 53.0 x 48.0 x 4 10K NTC Thermistor Configuration: 1S 1P Cell Type: GP404852 Cell Shape: Rectangular IEC 62133 Certified</p> 	<p>BL2600C18654S1PXX Lithium Ion 14.8VDC, 2600mAh Battery Pack Dimensions: 77 x 69 Fuel Gauge Configuration: 4S 1P Cell Type: ICR18650-26F Cell Shape: Cylindrical IEC 62133 Certified</p> 	<p>Type PZ0800 United Kingdom BS1363 13A/250V~</p> 	<p>Type 207 "Europlug" CEE7 Standard XVI (CEE 7/16) 2.5A/250V</p> 	<p>Type 2314 Schuko Europe CEE7 Standard sh 7 16A/250V</p> 	<p>Type 550 Australia, New Zealand AS/NZS 3112 10A/250V~</p> 
<p>Molex 3 Pin CPU Fan Connector Molded on 2464 18 AWG Black Cable</p> 	<p>BL2200F6034501S2XXXX Lithium Ion 3.7VDC, 2200mAh Battery Pack Dimensions: 51 x 34 x 13 Configuration: 1S 2P Cell Type: 603450 Cell Shape: Rectangular IEC 62133 Certified</p> 	<p>BL2600C1865004S1PG1 Lithium Ion 14.8VDC, 2600mAh Battery Pack Dimensions: 66 x 73.5 x 28.5 Fuel Gauge/Built In Charger Circuitry 4S 1P Cell Type: ICR18650-26F Cell Shape: Cylindrical IEC 62133 Certified</p> 	<p>Type 205 India IS 1293 6A/250V~</p> 	<p>Type 208 South Africa SABS 164-1 16A/250V~</p> 	<p>Type 219 Argentina IRAM 2073 10A/250V~</p> 	<p>Type 204B Brazil NBR 14136 10A/250V~</p> 
<p>Buzz Fuse Holder</p> 	<p>BL2600C1865001S2PXXXX Lithium Ion 3.7VDC, 5200mAh Battery Pack Dimensions: 19 x 68.5 x 37 Configuration: 1S 2P Cell Type: ICR18650-26F Cell Shape: Cylindrical IEC 62133 Certified</p> 	<p>GTM91128 Smart Battery Charger Available in versions delivering 4.2V, 8.4V, or 12.6V at 1A to address single or multiple battery configurations</p> 	<p>Type 602 China GB 1002 10A/250V~</p> 	<p>Type 377C Isreal 16A/250V~</p> 	<p>Type 2302 Italy CEI 23-16 10A/250V~</p> 	<p>Type 2313K Korea KS C 8305 16A/250V~</p> 